


## FIG. 231CT two hole strap for copper tubing



| Materials/Finishes: | Copper Epoxy Coated Copper Gard (231CT)  |  |
|---------------------|--|--|
| Variants:           | N/A  |  |
| Service:            | Designed as a light duty support for copper tubing. Attaches directly to horizontal or vertical structural member. |  |
| Approvals:          | Complies with Manufacturers' Standardization Society MSS SP-58 & SP-69 (Type# 26)                                  |  |
| Ordering:           | Specify figure number and tube size  |  |
| Notes:              | Available domestic   |  |

| TUBE<br>SIZE | TUBE<br>OD | A<br>HOLE<br>SIZE | В     | С     | WGT<br>EACH<br>(lbs) |
|--------------|------------|-------------------|-------|-------|----------------------|
| 1/4          | 0.375      | 3/16              | 1-3/4 | 1-1/8 | 0.01                 |
| 3/8          | 0.500      | 3/16              | 1-7/8 | 1-1/4 | 0.01                 |
| 1/2          | 0.625      | 3/16              | 2-1/8 | 1-1/2 | 0.01                 |
| 3/4          | 0.875      | 3/16              | 2-3/8 | 1-5/8 | 0.02                 |
| 1            | 1.125      | 3/16              | 2-7/8 | 2-1/4 | 0.02                 |
| 1-1/4        | 1.375      | 3/16              | 3-1/8 | 2-1/2 | 0.04                 |
| 1-1/2        | 1.625      | 7/32              | 3-5/8 | 2-3/4 | 0.05                 |
| 2            | 2.125      | 7/32              | 4-1/4 | 3-3/8 | 0.06                 |

| PROJECT INFORMATION                     | APPROVAL STAMP |  |
|---|----------------|--|
| Project:                                | Notes:         |  |
| Address:                                |                |  |
| Contractor:                             |                |  |
| Engineer:                               |                |  |
| Date:                                   |                |  |
| Approved Approved as Noted Not Approved |                |  |