

Multi-Conductor, Unshielded, Tray Cable

Type TC, 600V



WARNING: Cancer & Reproductive Harm
www.P65Warnings.ca.gov

PART NUMBER	NO. OF COND	AWG. SIZE	NOM O.D.	WEIGHT
			INCHES	POUNDS
18 AWG CONDUCTORS				
W181P-1416	2	18	0.255	33 lbs.
WI83C-1052	3	18	0.280	43 lbs.
W184C-1054	4	18	0.310	52 lbs.
W186C-1497	6	18	0.360	72 lbs.
WI18-08VNTC	8	18	0.380	89 lbs.
16 AWG CONDUCTORS				
W161P-1047	2	16	0.280	42 lbs.
WI16-03VNTC	3	16	0.310	55 lbs.
WI16-04VNTC	4	16	0.340	69 lbs.
WI16-06VNTC	6	16	0.390	96 lbs.
WI16-08VNTC	8	16	0.390	122 lbs.
14 AWG CONDUCTORS				
W141P-1110	2	14	0.285	62 lbs.
WI14-03VNTC	3	14	0.350	80 lbs.
WI14-04VNTC	4	14	0.380	99 lbs.
WI14-06VNTC	6	14	0.450	140 lbs.

Note: Other gauge sizes and conductor counts are available - contact your sales office.

Product Construction

CONDUCTOR:

- Stranded bare copper

Insulation:

- Flame-Retardant PVC with Nylon

JACKET:

- Sunlight Resistant PVC
- Suitable for use to 90C (dry)

APPLICATIONS:

- Indoors
- Outdoors
- Direct Burial
- In ducts, conduits or cable trays
- Aerially

STANDARDS:

- UL Type TC
- Approved for class 1 remote-control and signalling circuits (NEC Art 725)