



# Safety Data Sheet

## BOSS® 360 Sealant Siliconized Latex

### Section 1. Identification

Product Identifier BOSS® 360 Sealant Siliconized Latex  
Synonyms 36001  
Manufacturer Stock Numbers 02735WH10; C39018WH

Recommended use Refer to Technical Information  
Uses advised against Refer to Technical Information

#### Manufacturer Contact

Address Soudal Accumetric  
350 Ring Road  
Elizabethtown, KY, 42701  
USA

Phone  
(270) 769-3385

Emergency Phone  
(800) 424-9300  
CHEMTREC

Fax  
(270) 765-2412

### Section 2. Hazards Identification

Classification N/A  
Signal Word  
Pictogram  
Hazard Statements N/A  
Precautionary Statements  
Response N/A  
Prevention N/A  
Storage N/A  
Disposal N/A  
General If medical advice is needed, have product container or label at hand  
Keep out of reach of children

Read label before use

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

GHS Classification Not a hazardous substance or mixture.

GHS Label Element Not a hazardous substance or mixture.

Other hazards None known

### Section 3. Ingredients

CAS	Ingredient Name	Weight %
7632-00-0	Sodium nitrate	0.1% - Max
27138-31-4	Dipropylene glycol dibenzoate	1% - 5%
13463-67-7	Titanium Dioxide	1% - 5%
64742-46-7	Distillates (petroleum), hydrotreated middle	1% - 5%

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-Aid Measures

Ingestion No first aid should be needed.  
Skin Contact Wash affected area with soap and water.  
Inhalation Remove to fresh air. If symptoms persist, obtain appropriate medical attention.  
Eye Contact Immediately flush with large amounts of water. If irritation occurs, seek medical attention.

### Section 5. Fire Fighting Measures

Suitable Extinguishing Media Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog  
Unsuitable Extinguishing Media None known  
Special Fire Fighting Procedures Non-flammable (aqueous emulsion). After water evaporates, remaining material will burn. Breathing apparatus required when fighting fires in enclosed areas.  
Unusual Fire or Explosion Hazards Product will not burn, but may splatter if temperature exceeds boiling point of water. Dried solids can burn, giving off oxides of carbon.

### Section 6. Accidental Release Measures

Steps to be taken in case of spill or release Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment

recommendations described in Sections 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. For small spills, wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled material, even in small quantities, may present a slip hazard. Final cleaning may require the use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

## Section 7. Handling and Storage

Storage	Store in a cool dry place. Protect from freezing and excessive heat.
Handling	Avoid breathing vapors in top of shipping container. Keep container closed. Use with adequate ventilation. Avoid contact with skin and clothing. Wash thoroughly after handling.

## Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Sodium nitrate	N/A	N/A	N/A
	Dipropylene glycol dibenzoate	N/A	N/A	N/A
	Titanium Dioxide	10 mg/m3	15 mg/m3	N/A
	Distillates (petroleum), hydrotreated middle	5 mg/m3	5 mg/m3	10 mg/m3

  

Personal Protective Equipment	Goggles, Gloves
Ventilation	Local exhaust ventilation is recommended to maintain vapor level below TLV.
Respiratory protection	No respiratory protection should be needed with good local ventilation.
Eye Protection	Safety goggles or glasses with side shields are recommended.
Skin Protection	Impervious gloves are suggested.

## Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Refer to product label
Odor	Slight
Odor Threshold	N/A
Solubility	Dilutable in wet stage
Partition coefficient Water/n-octanol	N/A

VOC%	9.8 g/L
Viscosity	750,000 cPs
Specific Gravity	1.66
Density lbs/Gal	13.8
Pounds per Cubic Foot	103.63042
Flash Point	Not determined
FP Method	N/A
Ph	7.85
Melting Point	0C
Boiling Point	100C
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Slower than n-Butyl acetate
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not determined
Vapor Density	Lighter than air

Note The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

## Section 10. Stability and Reactivity

Hazardous polymerization Will not occur  
 Chemical Stability Stable  
 Conditions to Avoid None known  
 Materials to Avoid / Incompatibility None known

## Section 11. Toxicological Information

Special Hazard Information on Components No known applicable information.  
 Component Toxicology Information No known applicable information.

## Section 12. Ecological Information

Fate and Effects in Waste Complete information is not yet available.

Water Treatment Plants  
Environmental Effects Complete information is not yet available.  
Environmental Fate and Distribution Complete information is not yet available.

## Section 13. Disposal

**Waste Disposal Method** We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

## Section 14. Transport Information

UN Number N/A  
UN Proper Shipping Name Not regulated  
DOT Classification Not regulated  
Packing Group Not regulated  
Air Shipment (IATA) Not subject to IATA regulations.  
Ocean Shipment (IMDG) Not subject to IMDG code.

## Section 15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**TSCA Status** All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

**SARA Title III Section 302 Extremely Hazardous Substances** None

**SARA Title III Section 304 CERCLA Substances dangereuses** None

**SARA Title III Section 313 Toxic Chemicals** None present or none present in regulated quantities.

**California Proposition 65** This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known

## Section 16. Other Information

Revision Date 11/6/2015

## Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.